

Date of compilation: 08/08/2023 Version: 1

SECT	TON 1: IDENTIFICATION	OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1	Product identifier:	DB 8420 - Duobond UV Resin
	Other means of identification	tion:
	Non-applicable	
1.2	Relevant identified uses	of the substance or mixture and uses advised against:
	Relevant uses: Adhesive for	glass. For professional users only.
	Uses advised against: All use	es not specified in this section or in section 7.3
1.3	Details of the supplier of	the safety data sheet:
	DB-Imagineering BV	
	Laarakkerweg 10 5061 JR Oisterwijk - Netherla	ands
	Phone: 0135444440	
	info@db-img.com	DD Imagingaring DV
	Duobond is a brand name of	
1.4	Emergency telephone nu	mber: in case of emergency: 112
SECT	TION 2: HAZARDS IDENT	IFICATION

## 2.1 Classification of the substance or mixture:

## GB CLP Regulation:

Classification of this product has been carried out in accordance with GB CLP Regulation.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

# 2.2 Label elements:

# GB CLP Regulation:

# Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

#### **Precautionary statements:**

P273: Avoid release to the environment.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

## 2.3 Other hazards:

Product does not meet PBT/vPvB criteria

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substance:

Non-applicable

## 3.2 Mixture:

Chemical description: Acrylic copolymer in aqueous solution

Version: 1

## Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	Non-applicable	Methacrylic esther Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	2,5 - <5 %
CAS:	7473-98-5	2-hydroxy-2-methylpropiophenone Acute Tox. 4: H302; Aquatic Chronic 3: H412 - Warning	2,5 - <5 %
CAS:	3290-92-4	Propylidynetrimethyl trimethacrylate Aquatic Chronic 2: H411	1 - <2,5 %
CAS:	79-41-4	Methacrylic acid Acute Tox. 3: H311; Acute Tox. 4: H302+H332; Eye Dam. 1: H318; Skin Corr. 1A: H314; STOT SE 3: H335 - Danger 🛞 谷	<1 %
To ob	tain more informa	tion on the hazards of the substances consult sections 11, 12 and 16.	



Date of compilation: 08/08/2023 Version: 1

# SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

## By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

#### By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

#### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

## By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

## 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

## SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

## Unsuitable extinguishing media:

Non-applicable

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

## Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### For emergency responders:



Date of compilation: 08/08/2023 Version: 1

## SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Wear protective equipment. Keep unprotected persons away. See section 8.

## 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

## 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

## 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

#### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:5 °CMaximum Temp.:30 °CMaximum time:12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

## DNEL (Workers):

		Short e	xposure	Long ex	kposure
Identification		Systemic	Local	Systemic	Local
2-hydroxy-2-methylpropiophenone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7473-98-5	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
EC: 231-272-0	Inhalation	Non-applicable	Non-applicable	3.5 mg/m <sup>3</sup>	Non-applicable



## Date of compilation: 08/08/2023 Version: 1

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Propylidynetrimethyl trimethacrylate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 3290-92-4	Dermal	Non-applicable	Non-applicable	42 mg/kg	Non-applicable
EC: 221-950-4	Inhalation	Non-applicable	Non-applicable	14.81 mg/m <sup>3</sup>	Non-applicable
Methacrylic acid	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 79-41-4	Dermal	Non-applicable	Non-applicable	4.25 mg/kg	Non-applicable
EC: 201-204-4	Inhalation	Non-applicable	Non-applicable	29.6 mg/m <sup>3</sup>	88 mg/m <sup>3</sup>

#### **DNEL (General population):**

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
2-hydroxy-2-methylpropiophenone	Oral	Non-applicable	Non-applicable	0.4 mg/kg	Non-applicable
CAS: 7473-98-5	Dermal	Non-applicable	Non-applicable	0.5 mg/kg	Non-applicable
EC: 231-272-0	Inhalation	Non-applicable	Non-applicable	0.9 mg/m <sup>3</sup>	Non-applicable
Propylidynetrimethyl trimethacrylate	Oral	Non-applicable	Non-applicable	1.5 mg/kg	Non-applicable
CAS: 3290-92-4	Dermal	Non-applicable	Non-applicable	15 mg/kg	Non-applicable
EC: 221-950-4	Inhalation	Non-applicable	Non-applicable	2.6 mg/m <sup>3</sup>	Non-applicable
Methacrylic acid	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 79-41-4	Dermal	Non-applicable	Non-applicable	2.55 mg/kg	Non-applicable
EC: 201-204-4	Inhalation	Non-applicable	Non-applicable	6.3 mg/m <sup>3</sup>	6.55 mg/m <sup>3</sup>

#### PNEC:

Identification				
2-hydroxy-2-methylpropiophenone	STP	45 mg/L	Fresh water	0.002 mg/L
CAS: 7473-98-5	Soil	0.001 mg/kg	Marine water	0 mg/L
EC: 231-272-0	Intermittent	0.019 mg/L	Sediment (Fresh water)	0.009 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.001 mg/kg
Propylidynetrimethyl trimethacrylate	STP	10 mg/L	Fresh water	0.00276 mg/L
CAS: 3290-92-4	Soil	0.097 mg/kg	Marine water	0.000276 mg/L
EC: 221-950-4	Intermittent	0.02 mg/L	Sediment (Fresh water)	0.495 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.05 mg/kg

## 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Butyl, Breakthrough time: > 480 min, Thickness: 0.3 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



Recogning PPE       Remarks         Notice Controls/PERSONAL PROTECTION (continued)         Processing glasses against splash/projections       Claim daily and disinfect periodically according to the manufacturer's instruct Use if there is a risk of glashing.         E: Body protection         Reference of distributions for periods of prolonged against splash/projections         Reference of distributions. For protects of prolonged against splash work shoes         Program PPE       Remarks         Control of distributions in EV 50 503-2015, EV 503-2005, EV 1308-2013, EV 641-1994.         Note controls         Note controls         Replace before any orders of distortation. For protects of prolonged again to produce the produce the produce the regulatories in EV 50 503-2015, EV 503-2005, EV 1308-2013, EV 441-1994.         Description of the produce the produce of distortation. For protects of prolonged again splase before any orders of distortations. For protects of prolonged again to protection of the produce the produce the produce the regulatories in EV 150 20345-2012 yEV 1383-21-20         Entergency measure         Entergency measure       Sandards         Entergency measure       Sandards         Entergency measure       Sandards         Enter		pilation: 08/08/202		Version: 1				
Image: Standards         Environmental elasses against splash/projections.         Clean daily and disiriest periodically according to the manufacturer's instructure to the six of splashing.           E. Body protection         Processing and the synthesis of splashing.         Replece before any evidence of deterioration. For periods of prolonged explanations in the top of deterioration. For periods of prolonged explanations in the top of deterioration. For periods of prolonged explanations in the top of deterioration. For periods of prolonged explanations in the top of deterioration. For periods of prolonged explanations in the top of deteriorations. For periods of prolonged explanations in the top of deterioration in the top of deteriorations. For periods of prolonged explanations in the top of deterioration in the top of deterioratin the top of deterior	CTION	N 8: EXPOSURE	CONTR	OLS/PERSONAL PROTEC	TION (	(continued)		
Description       Description       Use if there is a risk of splashing.         E. Body protection       Preclagram       PPE       Remarks         Image: Control of the splashing of		Pictogram		PPE			Remarks	
E Body protection       Remarks         Protogram       PPE       Remarks         Work clothing       Replace before any evidence of deterioration. For periods of prolonged exp. to the product for professional/industrial users CEII II: recommended, 13086-2013, EN 450-252-033, EN 450-252-033, EN 50-052-033, EN 50-052-030, EN 5			Panoram	ic glasses against splash/projection:	s. Clean			
Image: Control of the product of professional/industrial users CE III is recommended, accordance with the regulations in RN ISO 5539-2013, RN 644:1994.           Image: Control of the product of professional/industrial users CE III is recommended. I scordance with the regulations in RN ISO 5539-2013, RN 644:1994.           F Additional emergency measures           Energency measure interpret in the product of professional/industrial users CE III is recommended. I so the product for professional/industrial users CE III is recommended. I so the product for professional/industrial users CE III is recommended. I so the product for professional/industrial users CE III is recommended. I so the product for professional/industrial users CE III is recommended. I so the product for professional/industrial users CE III is recommended. I so 3864-1:2011, ISO 3864-4:201           Emergency measure interpret is the product of professional/industrial users CE III is recommended. I so 3864-1:2011, ISO 3864-4:201         Events is recommended to avoid environment is in the product and its container. For additional information see subsection 7.1.0           Intervolation on basic physical and chemical properties:         For complete information see the product datasheet.           Appearance:         Coloress         Coloress           Physical state at 20 °C:         Liquid           Mild         Oddure thershold:         Non-applicable *           Volactifiery         S2 (P = S2 (P	E							
Work clothing         to the product for professional/industrial users CE III is recommended, in coordance with the regulations in EM ISO 6529:2005, EM 1506 5539:2005, EM 164:1994.           Anti-slip work shoes         Replace before any evidence of deterioration. For periods of prolonged expressional/industrial users CE III is recommended, in coordance with the regulations in EM ISO 529:2005, EM 13832:1:20           F Additional emergency measures         Emergency measure Standards         Emergency measure Standards         Emergency measure Standards           Emergency shower         ISO 3864-1:2011, ISO 3864-4:2011         Eyewash stations         DN 12 899           ISO 3864-1:2011, ISO 3864-4:2011         Eyewash stations         DN 12 899           ISO 3864-1:2011, ISO 3864-4:2011         Eyewash stations         DN 12 899           ISO 3864-1:2011, ISO 3864-4:201         Eyewash stations         DN 12 899           ISO 3864-1:2011, ISO 3864-4:201         Eyewash stations         DN 12 899           ISO 3864-1:2011, ISO 3864-4:201         Eyewash stations         DN 12 899           ISO 3864-1:2011, ISO 3864-4:201         Eyewash stations         DN 12 899           ISO 2895.2012, EW 2000         The Volatili Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:           V.O.C. (Supply):         43.53 % weight         V.O.C. (Supply):         A15.53 % organice           Information on basic physical and chemical properties		Pictogram		PPE			Remarks	
Anti-slip work shoes       to the product for professional/industrial users CE III is recommended, i accordance with the regulations in EN ISO 20345;2012 y EN 13832-1:200         F Additional emergency measures       Imagency measure       Standards       Emergency measure       Standards         Imagency measure       Iso 3664-1:2011, ISO 3864-4:2011       Imagency measure       Standards       DN 12 899         Iso 3664-1:2011, ISO 3864-4:2011       Imagency measure       Imagency measure       Imagency measure       Imagency measure         Environmental exposure controls:       In accordance with the community legislation for the protection of the environment it is recommended to avoid environments spillage of both the product and its container. For additional information see subsection 7.1.0.         The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:       V.O.C. (Supply):       43.53 % weight         V.O.C. (Supply):       43.53 % weight       V.O.C. (Supply):       43.53 % weight         V.O.C. (Supply):       43.53 % weight       V.O.C. (Supply):       Katadarde         Physical state at 20 °C:       466.83 kg/m³ (466.83 g/L)       Katadarde       Katadarde         Odour:       Not available       Odour:       Not available       Odour:       Katadarde         Odour:       Not available       Odour:       Not available       Not available       Notavailabl				Work clothing	t	o the product for professional/ir dance with the regulations in El	ndustrial users CE III is recommended, in N ISO 6529:2013, EN ISO 6530:2005, EN IS	
Image: Tempergency measure       Standards       Emergency measure       Standards         Image: Tempergency shower       Iso 3864-1:2011, ISO 3864-4:2011       Iso 3864-1:2011, ISO 3864-4:2011         Environmental exposure controls:         In accordance with the community legislation for the protection of the environment it is recommended to avoid environments spillage of both the product and its container. For additional information see usbesction 7.1.D         THON 9: PHYSICAL AND CHEMICAL PROPERTIES         For complete information see the product datasheet.         Appearance:         Colorless         Colorless         Colorless         Colorless         Colorless         Colorless         Colorless         Colorless         Color (ess       Colorle				Anti-slip work shoes	t	o the product for professional/ir	ndustrial users CE III is recommended, in	
Image: Ansize of the second state o	F	Additional emerge	ency mea	asures				
MSI 2358-1 ISO 3864-1:2011, ISO 3864-4:2011       Image: Composition of the sequence o		<b>*</b>		ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:201		Emergency measure	Standards	
In accordance with the community legislation for the protection of the environment it is recommended to avoid environment it spillage of both the product and its container. For additional information see subsection 7.1.0 The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012: V.O.C. (Supply): 43.53 % weight V.O.C. density at 20 °C: 466.83 kg/m³ (466.83 g/L) TOTON 9: PHYSICAL AND CHEMICAL PROPERTIES For complete information see the product datasheet. Appearance: Physical state at 20 °C: Liquid Appearance: Odour: Odour: Odour: Odour: Not available Odour: Mild Odour threshold: Volatility: Boiling point at atmospheric pressure: Sol of C: Vapour pressure at 20 °C: Vapour pressure at 20 °C: Non-applicable * Product description: Density at 20 °C: Non-applicable * Product description: Product description: Product description: Product description: Product description: Product description: Product description: Product description: Produc						Ŧ	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011	
Information on basic physical and chemical properties:For complete information see the product datasheet.Appearance:Physical state at 20 °C:LiquidAppearance:ColorlessColour:Not availableOdour:MildOdour threshold:Non-applicable *Volatility:521 PaBoiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:521 PaVapour pressure at 20 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Relative density at 20 °C:1.073					6.83 g/	L)		
For complete information see the product datasheet.         Appearance:         Physical state at 20 °C:       Liquid         Appearance:       Colorless         Colour:       Not available         Odour:       Mild         Odour threshold:       Non-applicable *         Volatility:       190 °C         Vapour pressure at 20 °C:       2861.09 Pa (2.86 kPa)         Vapour pressure at 20 °C:       Non-applicable *         Product description:       1072.5 kg/m³         Relative density at 20 °C:       1.073	CTION	N 9: PHYSICAL A	AND CH	EMICAL PROPERTIES				
Appearance:LiquidPhysical state at 20 °C:LiquidAppearance:ColorlessColour:Not availableOdour:Not availableOdour:MildOdour threshold:Non-applicable *Volatility:Soling point at atmospheric pressure:Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:Soling Pa (2.86 kPa)Vapour pressure at 20 °C:Non-applicable *Fvaporation rate at 20 °C:Non-applicable *Product description:I072.5 kg/m³Pelative density at 20 °C:1.073	L In	formation on bas	sic phys	ical and chemical propert	ies:			
Physical state at 20 °C:LiquidAppearance:ColorlessColour:Not availableOdour:MildOdour threshold:Non-applicable *Volatility:Solor of Color of	Foi	r complete informa	tion see	the product datasheet.				
Appearance:ColorlessAppearance:ColorlessColour:Not availableOdour:MildOdour threshold:Non-applicable *Volatility:Soling point at atmospheric pressure:Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:S21 PaVapour pressure at 20 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:I072.5 kg/m³Pelative density at 20 °C:1.073	Ар	pearance:						
Colour:Not availableOdour:MildOdour threshold:Non-applicable *Volatility:Non-applicable *Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:521 PaVapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:Von-applicable *Density at 20 °C:1072.5 kg/m³Relative density at 20 °C:1.073	Phy	ysical state at 20 <sup>o</sup>	C:	Lic	quid			
Odour:MildOdour threshold:Non-applicable *Volatility:Non-applicable *Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:521 PaVapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073	Ap	pearance:		Cc	Colorless			
Odour threshold:Non-applicable *Volatility:Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:521 PaVapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073	Co	lour:		No	Not available			
Volatility:Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:521 PaVapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073	Od	lour:		Mi	Mild			
Boiling point at atmospheric pressure:190 °CVapour pressure at 20 °C:521 PaVapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073	Od	lour threshold:		No	Non-applicable *			
Vapour pressure at 20 °C:521 PaVapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073	Vo	latility:						
Vapour pressure at 50 °C:2861.09 Pa (2.86 kPa)Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073		51	• •					
Evaporation rate at 20 °C:Non-applicable *Product description:1072.5 kg/m³Density at 20 °C:1.073		Vapour pressure at 20 °C:						
Product description:Density at 20 °C:1072.5 kg/m³Relative density at 20 °C:1.073								
Density at 20 °C:1072.5 kg/m³Relative density at 20 °C:1.073				No	on-applic	cable *		
Relative density at 20 °C: 1.073		-	n:					
		•			-	/m <sup>3</sup>		
Dynamic viscosity at 20 °C: Non-applicable *								
*Not relevant due to the nature of the product, not providing information property of its hazards.								

- CONTINUED ON NEXT PAGE -

Version: 1



Date of compilation: 08/08/2023 Version: 1

SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIE	S (continued)
	Kinematic viscosity at 20 °C:	Non-applicable *
	Kinematic viscosity at 40 °C:	Non-applicable *
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Non-applicable *
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	Non Flammable (>60 °C)
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	265 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard clas	sses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components: <b>Other safety characteristics:</b>	Non-applicable *
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing info	

# SECTION 10: STABILITY AND REACTIVITY

## 10.1 Reactivity:

10.5

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

## 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

## 10.3 Possibility of hazardous reactions:


Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

## **10.4** Conditions to avoid:

Applicable for handling and storage at room temperature:

	11 5	5 1			
	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
	Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
5	Incompatible materials	:			
	Acids	Wator	Ovidicing materials	Combustible materials	Othors

Avoid strong acids Not applicable Avoid direct impact Not applicable Avoid alkalis or strong bases	Acids	Water	Oxidising materials	Combustible materials	Others
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases





Date of compilation: 08/08/2023 Version: 1

# SECTION 10: STABILITY AND REACTIVITY (continued)

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

## SECTION 11: TOXICOLOGICAL INFORMATION

#### **11.1** Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Toluene (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

## Other information:

Non-applicable

- CONTINUED ON NEXT PAGE -

Version: 1



## Date of compilation: 08/08/2023 Version: 1

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

## Specific toxicology information on the substances:

Identification	Ac	ute toxicity	Genus
Methacrylic acid	LD50 oral	1320 mg/kg	Rat
CAS: 79-41-4	LD50 dermal	500 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
2-hydroxy-2-methylpropiophenone	LD50 oral	1694 mg/kg	Rat
CAS: 7473-98-5	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

# SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

## 12.1 Toxicity:

## Acute toxicity:

Identification	Concentration		Species	Genus	
2-hydroxy-2-methylpropiophenone L		>10 - 100 mg/L (96 h)		Fish	
CAS: 7473-98-5	EC50	>10 - 100 mg/L (48 h)		Crustacean	
	EC50	>10 - 100 mg/L (72 h)		Algae	
Propylidynetrimethyl trimethacrylate	LC50	2 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 3290-92-4	EC50	9.22 mg/L (48 h)	Daphnia magna	Crustacean	
	EC50	Non-applicable			
Methacrylic acid	LC50	Non-applicable			
CAS: 79-41-4	EC50	130 mg/L (48 h)	Daphnia magna	Crustacean	
	EC50	Non-applicable			

#### **Chronic toxicity:**

Identification	Concentration		Species	Genus	
Propylidynetrimethyl trimethacrylate	NOEC	0.138 mg/L	Pimephales promelas	Fish	
CAS: 3290-92-4	NOEC	Non-applicable			
Methacrylic acid	NOEC	Non-applicable			
CAS: 79-41-4	NOEC	53 mg/L	Daphnia magna	Crustacean	

# 12.2 Persistence and degradability:

## Substance-specific information:

Identification	Degradability		Biodegradability	
Methacrylic acid	BOD5	Non-applicable	Concentration	3 mg/L
CAS: 79-41-4	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	86 %

## 12.3 Bioaccumulative potential:


# Substance-specific information:

Identification		Bioaccumulation potential		
Methacrylic acid			BCF	2
CAS: 79-41-4			Pow Log	
			Potential	Low

## 12.4 Mobility in soil:

Identification	Absorpt	Absorption/desorption		Volatility	
Methacrylic acid	Кос	25	Henry	3.9E-2 Pa·m <sup>3</sup> /mol	
CAS: 79-41-4	Conclusion	Very High	Dry soil	Yes	
	Surface tension	2.912E-2 N/m (25 °C)	Moist soil	Yes	
Poculto of DBT and VDVR accordmont					

## 12.5 Results of PBT and vPvB assessment:





#### Date of compilation: 08/08/2023 Version: 1

# SECTION 12: ECOLOGICAL INFORMATION (continued)

## Product does not meet PBT/vPvB criteria

## 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

#### **13.1 Waste treatment methods:**

Code	Description	Waste class
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

#### Type of waste:

HP14 Ecotoxic

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

## **Regulations related to waste management:**

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

#### SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

## SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

#### The Control of Major Accident Hazards Regulations 2015:

Non-applicable

# Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

## Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits.

#### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:



CTION 16: OTHER INFORM	MATION (continued)
CTION 10: OTTER INFOR	ria 100 (containded)
This safety data sheet has 2020.	been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations
Texts of the legislative	phrases mentioned in section 2:
H412: Harmful to aquatic li	ife with long lasting effects.
Texts of the legislative	phrases mentioned in section 3:
The phrases indicated do n individual components which	ot refer to the product itself; they are present merely for informative purposes and refer to the ch appear in section 3
<b>GB CLP Regulation:</b>	
Aquatic Chronic 2: H411 - Aquatic Chronic 3: H412 - Eye Dam. 1: H318 - Cause Eye Irrit. 2: H319 - Causes	nful if swallowed. - Harmful if swallowed or if inhaled. Toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. es serious eye damage. s serious eye irritation. es severe skin burns and eye damage. s skin irritation.
Classification procedure	
Aquatic Chronic 3: Calculat	
Advice related to trainin	
Training is recommended ir	n order to prevent industrial risks for staff using this product and to facilitate their comprehension an data sheet, as well as the label on the product.
Principal bibliographica	
http://echa.europa.eu	
http://eur-lex.europa.eu	
Abbreviations and acror	nyms:
ADR: European agreement IMDG: International maritir IATA: International Air Trar ICAO: International Civil Av COD: Chemical Oxygen De BOD5: 5day biochemical ox BCF: Bioconcentration facto LD50: Lethal Dose 50 LC50: Lethal Concentration EC50: Effective concentrati LogPOW: Octanolwater par Koc: Partition coefficient of UFI: unique formula identif IARC: International Agency	nsport Association viation Organisation mand xygen demand or 1 50 ton 50 rtition coefficient 5 organic carbon fier

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -